


POWERLED LINEAR




Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.




6009CC




6012CC




6024CC



6036CC



6048CC




Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
6009CC	9"	3 W	250 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6012CC	12"	4 W	330 lm			
6024CC	24"	8 W	675 lm			
6036CC	36"	12 W	1080 lm			
6048CC	48"	16 W	1300 lm			

Specifications

Switch-selectable CCT
Dimmable with regular low-voltage electronic dimmers
Swivel mounting brackets included
Smooth linear wide spread
Multiple fixtures can be linked together (up to 200W)
5-year warranty

Finish

 **SBA** Sandblasted aluminum

Note

Junction box model 6000-JB or power cord model 6000-ACCPC are required for installation. Sold separately.

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

Accessories

6000-ACCCE06
6" extension cord
6000-ACCCE24
24" extension cord
6000-ACCCE60
60" extension cord
6000-ACCLR
Kit of left and right L connectors
6000-ACCPC
6' power cord
6000-JB
Junction box