

# Access

Our new LED Panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations.



| Model       | Size | Watts | Delivered lumens | LED lumens | CRI | Color °T | Voltage |
|-------------|------|-------|------------------|------------|-----|----------|---------|
| <b>2004</b> | 4"   | 11 W  | 770 lm           | 880 lm     | 80  | 3000 K   | 120 V   |
| <b>2006</b> | 6"   | 14 W  | 1100 lm          | 1120 lm    | 80  | 3000 K   | 120 V   |

### Specifications

Every fixture includes a junction box with an integrated driver  
 Over 35,000 hours of service life  
 Can be daisy chained  
 Superior LED performance and lifespan  
 Smooth 360° wide spread  
 Minimal heat emission  
 Frosted lens  
 Edge lit technology  
 Aluminum construction  
 Very low profile  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 Suitable for damp locations  
 Refer to website for dimmer compatibility  
 5-year warranty

### Finish

○ **WH** White

### Accessories

- REC-PT4-BB (2004)**  
4" recessed panel trim in brushed brass
- REC-PT4-BK (2004)**  
4" recessed panel trim in black
- REC-PT4-SN (2004)**  
4" recessed panel trim in satin nickel
- REC-EXT108**  
108" extension cable
- REC-EXT230**  
230" extension cable
- RFP-46**  
Rough-in plate
- RFP-UNI**  
Universal rough-in plate

### Order example

**2004-WH**  
White 4" round panel with 770 lumens at 3000 K

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

