Excel

LED panel lights are more accessible than ever before. Their sleek and minimal construction, combined with a two-hour fire-rated housing, offers a blend of security and modern clean design.

























Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
5004-DW*	4"	11 W	850 lm	80	3000 K - 2200 K	120 V
5004-FR-CC**	4"	11 W	825 lm		2700, 3000, 3500, 4000, 5000 K	
5006-FR-CC**	6"	14 W	1230 lm		4000, 3000 K	

^{*}Dim-to-warm technology dims from 3000 K to 2200 K

Specifications

Every fixture includes a junction box with an integrated driver

Over 35,000 hours of service life

Can be daisy chained

Superior LED performance and lifespan

Smooth 360° wide spread

Minimal heat emission

Frosted lens

Edge lit technology

Aluminum construction

Switch-selectable CCT: 2700 K/3000 K/

3500 K/4000 K/5000 K

Very low profile

IC certification (suitable for direct contact with insulation)

Air-tight certified as per ASTM E283-04

Suitable for wet locations

Refer to website for dimmer compatibility

Ideal operating temperature:

-20° to 40° C

x 1-3/8"

5-year warranty

Finish



○ WH White

Accessories

REC-TRIM4-BK (5004-DW only)

4" recessed panel trim in black

REC-TRIM4-GD (5004-DW only)

4" recessed panel trim in gold

REC-TRIM4-SN (5004-DW only)

4" recessed panel trim in satin nickel

REC-3K-EXT8FT (5004-DW only)

8-foot extension cable

REC-3K-EXT20FT (5004-DW only)

20-foot extension cable

REC-CC-EXT8FT (5004/6-FR only)

8-foot extension cable

REC-CC-EXT20FT (5004/6-FR only)

20-foot extension cable

RFP-46 (5004, 5006)

Rough-in plate

5004-FR


 $\times 1-3/8$ "


RFP-UNI (5004, 5006)

Universal rough-in plate


Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.





Ø4-1/4"



^{**2-}hour fire-rated without additional housing or hardware, in accordance with UL 263, ASTM E119, and CAN ULC S101