EXCEL



COLOR TEMPERATUR

LED panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations.












Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options 🗸
5003-CC	3"	8 W	600 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
5004-CC	4"	11 W	800 lm			
5005-CC	5"	12 W	900 lm			or
5006-CC	6"	14 W	1100 lm			V: 120 / 277 / 347V 0-10V dimming (Check for availability)
5004SQ-CC	4"	11 W	800 lm			
5004-FR-CC*	4"	11 W	825 lm	80		
5006-FR-CC*	6"	14 W	1230 lm	80		
5004-DW**	4"	11 W	850 lm	80	3000 K - 2200 K	120V


¹Model 5004-DW only


²Models 5004-FR-CC, 5006-FR-CC only

^{*2-}hour fire-rated without additional housing or hardware, in accordance with UL 263, ASTM E119, and CAN ULC S101


^{**}Dim-to-warm technology dims from 3000 K to 2200 K, Not available in multi-voltage



















Specifications

Every fixture includes a junction box with an integrated driver
Can be daisy chained
Smooth 360° wide spread
Frosted lens
Edge lit technology
Aluminum construction
Switch-selectable CCT
Very low profile
5-year warranty

Finish

5004-FR

BK Black (3", 4", and 6" models only)

SN Satin Nickel (5004, 5004-DW only)

Multi-voltage(V) ₩

WH White

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALS representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.

Accessories

REC-TRIM4-BK/GD/SN (5004)

4" recessed panel trim in black, gold, or satin nickel

REC-PT4-GD (5004-DW)

4" recessed panel trim in gold or satin nickel

REC-TRIM6-BK/GD/SN (5006)

6" recessed panel trim in black, gold, or satin nickel

5000-EXT8FT

8-foot extension cable

5000-EXT20FT

20-foot extension cable

RFP-23 (5003)

Rough-in plate

RFP-46 (5004, 5006)

Rough-in plate

RFP-58 (5005)

Rough-in plate

RFP-UNI (5003, 5004, 5006) Universal rough-in plate