



Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage 🖡
5003-CC	3"	8 W	600 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
5004-CC	4"	11 W	800 lm				
5005-CC	5"	12 W	900 lm				
5006-CC	6"	14 W	1100 lm				
5004SQ-CC*	4"	11 W	800 lm				
*0							

\*Square model

### Specifications

Every fixture includes a junction box with an integrated driver

Over 50,000 hours of service life

Can be daisy chained

Minimal heat emission

Edge lit technology

Cast aluminum construction

Switch-selectable CCT: 2700 K/3000 K/

3500 K/4000 K/5000 K Very low profile

5003-CC

5004-CC

IC certification (suitable for direct

contact with insulation)

Air-tight certified as per ASTM E283-04

Suitable for wet locations

Ideal operating temperature: -20° to 40° C Refer to website for dimmer compatibility 5-year warranty

Ø3-3/4"

Ø3-3/8'

Ø4-1/4

# Finish

BK Black
SN Satin Nickel (5004-cc only)
WH White

# Multi-voltage 🖡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALS representative for additional information and to confirm availability.

# Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.

# Accessories

**REC-TRIM4-BK (5004)** 4" recessed panel trim in black

REC-TRIM4-GD (5004) 4" recessed panel trim in gold

REC-TRIM4-SN (5004) 4" recessed panel trim in satin nickel

**REC-TRIM6-BK (5006)** 6" recessed panel trim in black

**REC-TRIM6-GD (5006)** 6" recessed panel trim in gold

REC-TRIM6-SN (5006)

6" recessed panel trim in satin nickel

5000-EXT8FT 8-foot extension cable

**5000-EXT20FT** 20-foot extension cable

RFP-23 (5003) Rough-in plate

**RFP-46 (5004, 5006)** Rough-in plate

RFP-58 (5005) Rough-in plate

x 1-7/16"

RFP-UNI (5003, 5004, 5006) Universal rough-in plate

#### Ø4-3/4' 5004SQ-CC 5005-CC 5006-CC Ø4-1/4" Ø5-3/8" 4-3/4" x 4-3/4" Ø6-7/8" Ø5-3/4" 12" 12' 12" 12' 12 12' 4-1/8" x 2-1/2" 4-1/8" x 2-1/2" 5" x 2-13/16" Ø5-3/4"

x 1-3/8"

x 1-3/8"

Ø6-7/8"

1 min

Ø6-1/2"