0 0 0 0 0 2700k 3000k 3500k 4000k 5000k **FUSION** COLOR TEMPERATURE The Fusion is a slim gimbal recessed panel with 5CCT, offering advanced lighting flexibility for precise illumination. Its gimbal design allows users to direct light as needed, and the 5CCT feature provides color temperature versatility, making the Fusion an ideal choice for both residential and commercial applications. WET 25°, SWIVEL/DIRECTIONAL AIR TIGHT **GPNX-CC** IC RATED T24 JA8 Certified 123 CED Intertek energy


Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options F
GPN4-CC	4"	10 W	850 lm	90	2700, 3000, 3500,	120V TRIAC dimming
GPN6-CC	6"	13 W	1050 lm		4000, 5000 K	TRIAC unining
						or

V: 120/277/347V 0-10V dimming (Check for availability)



Ø4-1/4"







Specifications

Every fixture includes a junction box with an integrated driver Switch-selectable CCT 110° beam angle 25° tilting, 360° rotation Cast aluminum construction 5-year warranty

Finish

BK Black

WH White

Accessories

RFP-UNI Universal rough-in plate

RFP-46 Rough-in plate for 4" and 6" models

GPN-CC-EXT8FT 8-foot extension cable

GPN-CC-EXT20FT

20-foot extension cable

Multi-voltage (V) 🖡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALS representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.