

Scope

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.

NEW WET ENERGY STAR Intertek IC RATED T24 JA8 CERTIFIED

30° SWIVEL/DIRECTIONAL AIR TIGHT

2700k 3000k 3500k 4000k 5000k COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
GMB2-CC	2"	8 W	725 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
LEDDOWNG3-CC	3"	8 W	680 lm				
GMB4-CC	4"	11 W	810 lm				

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained (3" and 4" models only)
 Superior LED performance and lifespan
 30° tilting, 360° rotation
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 Low profile
 40° beam spread
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 JA8 Certified
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature: -20° to 40° C
 FT6 rated cable
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel (3" and 4" models only)
- **WH** White

Accessories

- RFP-UNI**
Universal rough-in plate (3" and 4" models)
- RFP-GMB2**
Rough-in plate (GMB2-CC)
- RFP-23**
Rough-in plate (LEDDOWNG3-CC)
- RFP-46**
Rough-in plate (GMB4-CC)
- REC-CC-EXT8FT**
8-foot extension cable
- REC-CC-EXT20FT**
20-foot extension cable

Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

