

Scope

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.

UPGRADE  WET   **IC** RATED **JA8** CERTIFIED

 30° SWIVEL/DIRECTIONAL  AIR TIGHT  2700k 3000k 3500k 4000k 5000k COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
GMB2-CC	2"	8 W	725 lm	900 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
LEDDOWNG3-CC	3"	8 W	680 lm	750 lm			
LEDDOWNG4-CC	4"	8 W	680 lm	750 lm			
GMB4-CC	4"	11 W	810 lm	1000 lm			

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained (3" and 4" models only)
 Superior LED performance and lifespan
 30° tilting, 360° rotation
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 Low profile
 40° beam spread
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 JA8 Certified
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature: -20° to 40° C
 FT6 rated cable
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel (3" and 4" models only)
- **WH** White



Accessories

- RFP-UNI**
Universal rough-in plate (3" and 4" models)
- RFP-GMB2**
Rough-in plate (GMB2-CC)
- RFP-23**
Rough-in plate (LEDDOWNG3-CC and LEDDOWNG4-CC)
- RFP-46**
Rough-in plate (GMB4-CC)



Note

Other color °T, finishes, and voltage options are available but may require MOQ's and longer lead times. Please contact your DALI representative for more information.



GMB2-CC Ø2 1/4" 



LEDDOWNG3-CC Ø2 3/4" 



LEDDOWNG4-CC Ø2 3/4" 



GMB4-CC Ø4 1/4" 

