

INDIRECT

Imagine being able to create the perfect mood when dimming your lights. This is now possible with our Dim to Warm concept, generating a warm, exquisite glow to set the tone for your evening.



DAMP



WARM DIMMING



AIR TIGHT

IC

RATED



IND4-DW

IND6-DW



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
IND4-DW	4"	9 W	500 lm	80	3000 K - 2200 K	120 V
IND6-DW	6"	12 W	750 lm			

IND4-DW

Ø4-3/8"




1-1/2"

Ø4-1/4"

IND6-DW

Ø6-1/4"



2"

Ø6-3/4"

**Specifications**

Every fixture includes a junction box with integrated dimmable driver

Can be daisy chained

Dim-to-warm technology, dims from 3000 K to 2200 K to mimic incandescent light

Smooth 360° wide spread

Dome reflector

110° beam spread

Indirect lighting design with glare reduction

Aluminum construction

5-year warranty

Finish

○ **WH** White

Accessories**RFP-UNI**

Universal rough-in plate

RFP-46

Rough-in plate for 4" and 6" models

REC-3K-EXT8FT

8-foot extension cable

REC-3K-EXT20FT

20-foot extension cable

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.