

## Regressed gimbal downlight with thin trim

This versatile modern thin-trim 2-, 4-, and 6-inch gimbal with multi-directional adjustable swivel produces high light output with minimal glare as a result of its regressed light source. Ideal for general lighting or for areas requiring a directional light to showcase unique elements or to create dramatic wall-wash effects.



WET



LOW-GLARE



SWIVEL/DIRECTIONAL



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>RGM2-3K</b>	2"	8 W	660 lm	800 lm	90	3000 K	120 V
<b>RGM4-3K</b>	4"	12 W	1050 lm	1400 lm	90	3000 K	120 V
<b>RGM6-3K</b>	6"	15 W	1270 lm	1700 lm	90	3000 K	120 V

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Can be daisy chained  
 Superior LED performance and lifespan  
 Regressed light source  
 Minimal heat emission  
 Aluminum construction  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 40° beam angle  
 30° tilting, 360° rotation  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature:  
 -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Accessories

- RFP-UNI**  
Universal rough-in plate
- RFP-23**  
Rough-in plate for 2" and 3" models
- RFP-46**  
Rough-in plate for 4" and 6" models

### Order example

**RGM6-3K-SN**  
 6" gimbal recessed downlight with 1270 Lumens at 3000 K in a satin nickel finish

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

