

SCOPE

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.




Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
GMB2-CC	2"	8 W	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
LEDDOWNG3-CC	3"	8 W	800 lm			or
GMB4-CC	4"	11 W	995 lm			V: 120 / 277 / 347V 0-10V dimming (Check for availability)

GMB2-CC

Ø2-1/4"



1-5/8"




Ø2-1/2"

GMB4-CC

Ø4-1/4"



1-5/8"




Ø4-7/8"

LEDDOWNG3-CC

Ø2-3/4"



2"



Ø3-1/4"

**Specifications**

Every fixture includes a junction box with integrated dimmable driver

Can be daisy chained (3" and 4" models only)

30° tilting, 360° rotation

Aluminum construction

Switch-selectable CCT

Low profile

40° beam spread

5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel (GMB4-CC only)
- **WH** White

Accessories**RFP-UNI**

Universal rough-in plate for 3" and 4" models

RFP-GMB2

Rough-in plate for GMB2-CC

RFP-23

Rough-in plate for LEDDOWNG3-CC

RFP-46

Rough-in plate for GMB4-CC

REC-CC-EXT8FT

8-foot extension cable

REC-CC-EXT20FT

20-foot extension cable

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.