

HILUX

DALS' high-powered recessed downlight is a go-to for your commercial projects. With its five color temperatures to choose from, a cast aluminum housing, high lumen output, and indoor/outdoor rating, this can be installed just about anywhere. From clinics to schools and hotels to boutiques, this is the only recessed fixture you will need.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
HPD4-CC	4"	20 W	1680 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
HPD6-CC	6"	30 W	2805 lm			
HPD8-CC	8"	40 W	3270 lm			or V: 120 / 277 / 347V 0-10V dimming (Check for availability)

HPD4-CCØ4-1/4" 

2-1/8"

Ø5"

HPD6-CCØ6-1/2" 

2-1/2"

Ø7-1/4"

HPD8-CCØ7-1/2" 

2-1/2"

Ø8-3/4"

**Specifications**

Every fixture includes a junction box with an integrated driver

Switch-selectable CCT

Smooth 360° wide spread

90° beam angle

Cast aluminum construction

5-year warranty

Finish

● **BK** Black (HPD4 and HPD6 only)

○ **WH** White

Accessories**RFP-46**

Rough-in plate for HPD4, HPD6

RFP-58

Rough-in plate for HPD8

RFP-UNI

Universal rough-in plate

REC-CC-EXT8FT

8-foot extension cable

REC-CC-EXT20FT

20-foot extension cable

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.