


Delta

Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. With 4 sizes to choose from, every application is covered.

UPGRADE



T24
JA8
CERTIFIED



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
CFLEDR06-CC	6"	11 W	700 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
CFLEDR10-CC	10"	17 W	1200 lm			
CFLEDR14-CC	14"	26 W	1700 lm			
CFLEDR18-CC	18"	30 W	2100 lm			
CFLEDR24-CC	24"	40 W	3000 lm			

Specifications

Integrated dimmable driver
 Over 50,000 hours of service life
 Switch-selectable CCT: 2700 K/
 3000 K/3500 K/4000 K/5000 K in canopy
 Smooth 360° wide spread
 Minimal heat emission
 Frosted lens
 Edge-lit technology
 Cast aluminum construction
 Suitable for outdoor locations
 on covered ceilings only
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish


- **BK** Black
- **GD** Gold (6, 10, 14" models only)
- **SN** Satin Nickel (6, 10, 14" models only)
- **WH** White

Note


Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.




CFLEDR06-CC




CFLEDR10-CC



CFLEDR14-CC



CFLEDR18-CC



CFLEDR24-CC

