

MODEL CFLEDR10-CC NAME DELTA SERIES 10" Round Flush Mount


Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. Can be installed indoors or out and icludes five switch-selectable CCT settings.



Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124th Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com **dals.com**


PROJECT:	TYPE:
DATE:	QTY:
NOTES:	





QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM Angle	LIGHT DIRECTION	FINISH
10" *Lumen c	17W butput measured at	880lm t 3000K	2700K 3000K 3500K 4000K 5000K	90	120V	110°	Straight	 White Black Satin nickel Gold



CONSTRUCTION	Lens Frosted Lens material PC	Finish type Paint (BK, WH) Electroplate (SN, BB) Housing material Cast aluminum	Type of LED Edge lit SMD Mounting Twist bracket
RATINGS	Placement Indoor/outdoor Location Wet (Covered ceiling mounted only)	Lifespan 50,000 hrs. Certifications ETL, JA8, FCC, ES	IP rating IP44 Operating temperature -20° to 40° C
ACCESSORIES -		ADAPTERS -	

WHAT'S IN THE BOX

LED flush mount fixture Mounting bracket Mounting hardware Wire nuts Instruction sheet

dals		Canada 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1	U.S.A. 4383, NW 124 th Ave Coral Springs, Flor		877.430.1818 info@dals.com dals.com	ļ
ELECTRICAL DETAILS	Input voltage 108-120V	Output current -	Power factor 90%	Driver ty Driver on	-	
	Output voltage -	LED model # 2835	THD harmonic distortion <30%	Binning type 3 SDCM		
FEATURES	Integrated dimmable driver	Smooth 360° wide spread	Switch-selectable CCT: 2700K/ 3000 K/ 3500 K/ 4000 K/ 5000 K			
	Superior LED performance and lifespan	Minimal heat emission Edge-lit technology				
WARRANTY	-	arranty from the date of purchas ement of defective parts of the				

covers repairs or replacement of defective parts of the housing optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE		RANGE (%) MAX	MAX LOAD
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	Compatible	0	100	15
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	3	100	9
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	3	100	9
Lutron	STCL-153PH-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	0	95	9
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	Compatible	0	95	9
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	Compatible	5	94	15
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	Compatible	5	100	9
Leviton	IPL06-10Z*	Triac, 150 W Dimmable CFL/LED	Compatible	5	100	9
Leviton	DSL06-1LZ*	Triac, 150 W Dimmable CFL/LED	Compatible	0	100	9
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	Compatible	0	100	18
Legrand	RHCL453PNICCV4*	Triac, 450W Dimmable CFL/LED	Compatible	0	100	26
Legrand	ADTP703TUM4*	Triac,450W Dimmable CFL/LED	Compatible	9	78	26
Legrand	ADPD453LM2*	Triac,450W Dimmable CFL/LED	Compatible	0	100	26
Legrand	RHL373PW*	Triac, 250W LED	Compatible	0	99	15
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0	100	7
Control 4	C4-FPD120-WH	Triac, 200W LED	Compatible	0	100	12
Commercial Electric	HPDA311CWB*	Triac, 150W LED & CFL	Compatible	0	100	9
tp-link	HS220*	Triac, 150 W, Dimmable LED (MLV)	Compatible	0	100	9
Leviton	RDL06-10Z	Triac, 150W LED & CFL	Compatible	8	100	9

* Minimal buzzing noise may occur with some dimmers