

Brooklyn

The key design element of our LED wall mount is the removable lens. This feature allows for three distinctive styles during installation.



ADA
COMPLIANT



T24
JA8
CERTIFIED



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
LEDWALL-B	11-3/4"	29 W	2100 lm	90	3000 K	120 V - 277 V

Specifications

Square housing made of extruded aluminum
 Fixture canopy made of die-cast aluminum
 LED module is mounted on an aluminum heat sink to maximize heat dissipation and extend product life

The square wall mount comes with 3 optical options:

- Bright aluminum reflector that provides a 45° beam spread
- Frosted glass lens to allow a wider beam spread
- Die-caster aluminum cap to allow a down only version

The LED board is sealed with a clear, tempered glass lens to ensure weatherproof operation
 Baked powder paint coat for a highly durable finish
 Integrated dimmable driver
 JA8 certified
 Energy Star certified
 ADA compliant
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **WH** White

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

LEDWALL-B

