

## **LEDWALL-A** MODEL NAME ADEN

**Round Cylinder With Multiple Lighting Options** 

The key design element of our new LED cylinder is the removable lens. This feature allows for three distinctive styles during installation.





Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1

U.S.A. 4383, NW 124<sup>th</sup> Ave., Coral Springs, Florida 33065

877.430.1818 info@dals.com dals.com

PROJECT:	TYPE:
DATE	071/
DATE:	QTY:
NATEC	
NOTES:	






**←** 4-9/16" →

## QUICK SPECS

S	ZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	LIGHT DIRECTION	FINISH
4"		29W	2100lm	3000K	90	120V-277V	45° or 115°	Up and down	Black

\*Lumen output measured at 3000K



	Clear or frosted	Powder coated	COB
	<b>Lens material</b> Glass	Housing material Aluminum	<b>Mounting</b> Octo Jbox
RATINGS	<b>Placement</b> Indoor/outdoor	<b>Lifespan</b> 50,000 hrs.	<b>IP rating</b> IP65
	<b>Location</b> Wet	<b>Certifications</b> ETL, JA8, ES	<b>Operating</b> temperatur -30° to 40° (
ACCESSORIES		ADAPTERS	
-		-	

## WHAT'S IN THE BOX

LED wall sconce fixture Mounting bracket Mounting hardware Wire nuts Instruction sheet

dals		<b>Canada</b> 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1	<b>U.S.A.</b> 4383, NW 124 <sup>th</sup> Av Coral Springs, Flo	- /	877.430.1818 info@dals.com <b>dals.com</b>	
ELECTRICAL Input voltage DETAILS 120-277V Output voltage 24-42V		<b>Output current</b> 700mA <b>LED model #</b> COB	Power factor 90% THD harmonic distortion <20%	<b>Driver type</b> Constant current <b>Binning type</b> 3 SCDM		
FEATURESCylinder comes with 3 optical options: • Bright aluminum reflector that provides a 45° beam spread • Frosted glass lens		to allow a wider beam spread • Die-cast aluminum cap to allow a down light only version Cylindrical housing made of extruded aluminum The LED board is sealed with a clear tempered		glass lens to ensure weatherproof operation Driver installs in junction box		Not compatible with shallow junction boxes
WARRANTY	DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to <u>info@dals.com</u> .					

## **RECOMMENDED DIMMER LIST\***

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING RANGE (%) MIN MAX	MAX LOAD
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	7 100	10
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	1 100	9
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	3 100	9
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0 100	4
Lutron	DVSTV (0-10 V Controls)	960W, 8 A, 120-277V	Compatible	12 93	33

 $^{\ast}$  Minimal buzzing noise may occur with some dimmers