

## RGR square series

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

UPGRADE



WET



LOW-GLARE



ENERGY STAR

IC

RATED



AIR TIGHT

JA8

CERTIFIED



Intertek



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>RGR2SQ-CC</b>	2"	8 W	600 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>RGR4SQ-CC</b>	4"	14 W	1100 lm	1200 lm			120 V
<b>RGR4SQ-CC-V-WH*</b>	4"	14, 15 W	1100 lm	1200 lm			120, 277 V
<b>RGR6SQ-CC</b>	6"	20 W	1600 lm	1900 lm			120 V

\* 0-10V dimming, white finish only

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Can be daisy chained (4" and 6" models only)  
 Superior LED performance and lifespan  
 Regressed light source  
 Minimal heat emission  
 Aluminum construction  
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 40° beam angle  
 Suitable for wet locations  
 JA8 Certified  
 Ideal operating temperature: -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Accessories

**RFP-23**  
 Rough-in plate for RGR2SQ

**RFP-46**  
 Rough-in plate for RGR4SQ & RGR6SQ

### Note

Other color °T, finishes, and voltage options are available but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

