

RGR series

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

NEW WET LOW-GLARE ENERGY STAR IC RATED AIR TIGHT T24 JA8 CERTIFIED

Intertek 2700k 3000k 3500k 4000k 5000k COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
RGR1-CC	1"	6 W	500 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
RGR2-CC	2"	8 W	600 lm				
RGR2HP-CC	2"	15 W	1080 lm				
RGR4-CC	4"	14 W	1100 lm				
RGR4HP-CC	4"	20 W	1560 lm				
RGR6-CC	6"	20 W	1600 lm				

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Regressed light source
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K / 3000 K / 3500 K / 4000 K / 5000 K
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 40° beam angle
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature: -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **WH** White

Accessories

- RFP-23**
Rough-in plate for RGR2
- RFP-35**
Rough-in plate for RGR4
- RFP-46**
Rough-in plate for RGR6
- REC-CC-EXT8FT**
8-foot extension cable
- REC-CC-EXT20FT**
20-foot extension cable

Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

