

RGR

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

RGR6-CC



RGR1-CC



RGR2-CC



RGR4-CC





*Energy Star certification applies to all models except RGR1-CC

RGR

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.



WET



LOW-GLARE



AIR TIGHT



RATED



CERTIFIED



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
RGR1-CC	1"	6 W	450 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
RGR2-CC	2"	8 W	720 lm			
RGR2HP-CC	2"	14 W	1155 lm			or
RGR2SQ-CC	2"	8 W	735 lm			V: 120 / 277 / 347V
RGR4-CC	4"	14 W	1185 lm			0-10V dimming
RGR4HP-CC	4"	20 W	1650 lm			(Check for availability)
RGR4SQ-CC	4"	14 W	1140 lm			
RGR6-CC	6"	20 W	1940 lm			
RGR6SQ-CC	6"	20 W	1940 lm			

*Energy Star certification applies to all models except RGR1-CC

RGR1-CC

Ø1-3/4"



Ø2-1/4"

RGR2-CC

Ø2-3/4"



Ø3-1/8"

RGR2HP-CC

Ø2-3/4"



Ø3-3/16"

RGR4-CC

Ø3-1/2"



Ø4-1/2"

RGR4HP-CC

Ø3-1/2"



Ø4-9/16"

RGR6-CC


Ø6-1/2"



Ø7"

RGR2SQ-CC

Ø2-3/4"




3-1/8" x 3-1/8"

RGR4SQ-CC

4" x 4"


Ø4-1/4"



4-1/2" x 4-1/2"

RGR6SQ-CC

Ø6-1/2"



7" x 7"

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained (4" and 6" models only)
 Aluminum construction
 Switch-selectable CCT
 40° beam angle
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel (Not available for RGR1-CC and HP versions)
- **WH** White

Accessories**RFP-01**

Rough-in plate for RGR1

RFP-23

Rough-in plate for RGR2, RGR2HP, RGR2SQ

RFP-35

Rough-in plate for RGR4, RGR4HP

RFP-46

Rough-in plate for RGR6, RGR4SQ & RGR6SQ

RFP-UNI

Universal rough-in plate for RGR2, RGR2HP, RGR2SQ, RGR4SQ, RGR6, RGR6SQ

REC-CC-EXT8FT, REC-CC-EXT20FT

8 ft and 20 ft extension cables

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.