

Aperture

From residential use to art galleries & boutiques, our multi-function downlight will check all the boxes. You can choose between recessed or spotlight, control the beam angle, and tilt the head 90 degrees.

NEW

2700k 3000k 3500k 4000k 5000k

COLOR TEMPERATURE

ETL Intertek

ENERGY STAR

T24 JA8 CERTIFIED

W MULTI-WATT*

AIR TIGHT

IC RATED



*Model MFD03-MW-CC only

Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
MFD03-CC	3"	8 W	600 lm	90	2700, 3000, 3500,	120 V
MFD03-MW-CC	3"	8, 10, 12 W	600, 800, 1000 lm		4000, 5000 K	

Specifications

Over 50,000 hours of service life
 Every fixture includes a junction box with integrated dimmable driver
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 Multi-watt output allows you to choose from three wattage settings for customizable brightness
 Can be daisy chained
 Superior LED performance and lifespan
 90° tilting, 360° rotation
 Adjustable beam angle from 30° to 60°
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 Refer to website for dimmer compatibility
 5-year warranty

Finish

- **BK** Black
- **WH** White

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

Accessories

- RFP-UNI**
Universal rough-in plate
- REC-CC-EXT8FT**
8-foot extension cable
- REC-CC-EXT20FT**
20-foot extension cable

MFD03-CC

Ø3-3/8" 

