

Etch

The Etch range of circular recessed downlights, characterised by a deep-set LED position, provides a functional solution to general lighting without the uncomfortable glare.

NEW WET LOW-GLARE Intertek IC RATED

AIR TIGHT COLOR TEMPERATURE 2700k 3000k 3500k 4000k 5000k ENERGY STAR



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
DDP4-CC	4"	15 W	1000 lm	90	2700, 3000, 3500,	120 V
DDP6-CC	6"	20 W	1500 lm		4000, 5000 K	

Specifications

Every fixture includes a junction box with an integrated driver
 Over 50,000 hours of service life
 Can be daisy chained
 Smooth 360° wide spread
 125° beam angle
 Minimal heat emission
 Frosted lens
 Edge lit technology
 Cast aluminum construction
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 Easy-access CCT switch on panel wire
 Very low profile
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 Suitable for wet locations
 Ideal operating temperature: -20° to 40° C
 Refer to website for dimmer compatibility
 5-year warranty

Finish

○ **WH** White

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

Order example

DDP4-CC-WH

White 4" deep regressed panel with 1000 lumens at 3000 K

Accessories

RFP-46

Rough-in plate

RFP-UNI

Universal rough-in plate

DDP4-TRIM-BK

4" recessed panel trim in black


DDP6-TRIM-BK

6" recessed panel trim in black



DDP4-CC

Ø4-1/4"



DDP6-CC

Ø6-1/2"

