


# NOTCH


The Notch series of recessed downlights is characterized by a deep-set LED position which greatly reduces glare, neatly packaged in a price-conscious solution to general lighting.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
DRR2-CC	2"	9 W	500 lm	90	2700, 3000, 3500, 4000, 5000 K	<b>120V TRIAC dimming</b>
DRR4-CC	4"	11 W	800 lm			or
DRR6-CC	6"	14 W	1000 lm			<b>V: 120 / 277 / 347V 0-10V dimming</b> (Check for availability)

**DRR2-CC**

Ø2-3/4"



1-7/8"

Ø3-1/8"

**DRR4-CC**

Ø4-1/4"




1-13/16"

Ø4-3/4"

**DRR6-CC**

Ø6-1/2"



1-13/16"

Ø6-7/8"



### Specifications

Every fixture includes a junction box with an integrated driver

Can be daisy chained

Smooth 360° wide spread

100° beam angle

Frosted lens

Edge lit technology

Switch-selectable CCT

5-year warranty

### Finish

○ **WH** White

### Accessories

**RFP-23**  
Rough-in plate (DRR2)

**RFP-46**  
Rough-in plate (DRR4, DRR6)

**RFP-UNI**  
Universal rough-in plate (DRR4, DRR6)

**DRR4-TRIM-BK**  
4" recessed panel trim in black

**DRR4-TRIM-SBA**  
4" recessed panel trim in sandblasted aluminum

**DRR6-TRIM-BK**  
6" recessed panel trim in black

**DRR6-TRIM-SBA**  
6" recessed panel trim in sandblasted aluminum

**REC-CC-EXT8FT**  
8-foot extension cable

**REC-CC-EXT20FT**  
20-foot extension cable

### Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

### Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.