

# Revolve

Our Recessed family has grown with a new range of adjustable downlights. The effortless design and high functionality of these fixtures are sure to make a welcome addition in any room.

- UPGRADE**
- WET**
- LOW-GLARE**
- ENERGY STAR**
- ETL US Intertek**
- IC RATED**
- T24 JA8 CERTIFIED**
- WARM DIMMING\***
- 30° SWIVEL/DIRECTIONAL**
- AIR TIGHT**
- COLOR TEMPERATURE**  
2700k 3000k 3500k 4000k 5000k



\*Models GBR35-DW , GBR04-DW, GBR06-DW only

Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
<b>GBR35-CC</b>	3.5"	12 W	860 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
<b>GBR04-CC</b>	4"	15 W	1240 lm				
<b>GBR06-CC</b>	6"	20 W	1500 lm				
<b>GBR35-DW</b>	3.5"	12 W	860 lm	90	3000 K - 2200 K		
<b>GBR04-DW</b>	4"	15 W	1240 lm				
<b>GBR06-DW</b>	6"	20 W	1500 lm				

### Specifications

Every fixture includes a junction box with an integrated driver  
 Over 50,000 hours service life  
 Switch-selectable CCT: 2700 K/ 3000 K/3500 K/4000 K/5000 K (GBRXX-CC models only)  
 Dim-to-warm technology, dims from 3000 K to 2200 K to mimic incandescent light (GBRXX-DW models only)  
 40° beam angle  
 30° tilting, 360° rotation  
 Cast aluminum construction  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 5-year warranty

### Finish

- **BK** Black (GBRXX-CC models only)
- **WH** White

### Accessories

- RFP-35 (GBR35)**  
Rough-in plate
- RFP-UNI (GBR04, GBR06)**  
Universal rough-in plate
- RFP-46 (GBR04, GBR06)**  
Rough-in plate
- REC-CC-EXT8FT (GBRXX-CC)**  
8-foot extension cable
- REC-CC-EXT20FT (GBRXX-CC)**  
20-foot extension cable
- REC-3K-EXT8FT (GBRXX-DW)**  
8-foot extension cable
- REC-3K-EXT20FT (GBRXX-DW)**  
20-foot extension cable

### Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

### Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

