

ETCH

The Etch range of circular recessed downlights, characterized by a deep-set LED position, provides a functional solution to general lighting without the uncomfortable glare.



DDP4-CC

DDP6-CC

DCP-DDP4




Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
DDP4-CC	4"	14 W	1430 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
DDP6-CC	6"	20 W	2045 lm			or
						V: 120 / 277 / 347V 0-10V dimming (Check for availability)
DCP-DDP4	4"	15 W	1000 lm	90	RGB + 2700 K - 6500 K	120 V
DCP-DDP6	6"	20 W	1500 lm			

*Models DCP-DDP4, DCP-DDP6 only


*Models DDP4-CC and DDP6-CC are Energy Star certified

DDP4-CC, DCP-DDP4

Ø4-1/4"

**DDP6-CC, DCP-DDP6**

Ø6-1/2"

**Specifications**

Every fixture includes a junction box with an integrated driver
 Can be daisy chained
 Smooth 360° wide spread
 125° beam angle
 Frosted lens
 Backlit technology
 Cast aluminum construction
 Switch-selectable CCT
 Full color spectrum and 2700–6500K in pure whites (DCP-DDP4, DCP-DDP6 only)
 Dimmable via the DALI Connect app and the DCP-RMCT remote (DCP-DDP4, DCP-DDP6 only)
 5-year warranty

Finish

○ **WH** White

Accessories**RFP-46**

Rough-in plate

RFP-UNI

Universal rough-in plate

DDP4-TRIM-BK

4" recessed panel trim in black

DDP6-TRIM-BK

6" recessed panel trim in black

REC-CC-EXT8FT, REC-CC-EXT20FT

8 ft and 20 ft extension cables for CC models

DCP-RMCT

Smart remote for DCP-DDP4 and DCP-DDP6

DCP-HUBV2

DALI Connect Pro Hub for DCP-DDP4 and DCP-DDP6

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.