



DALS LIGHTING

Canada
80, de la Seigneurie blvd., E.
Blainville, Quebec J7C 4N1

U.S.A.
4383, NW 124th Ave.,
Coral Springs, Florida 33065

877.430.1818
info@dals.com
dals.com

MODEL DDP4-CC

NAME Etch

4" Deep regressed panel 5CCT

The Etch range of circular recessed downlights, characterised by a deep-set LED position, provides a functional solution to general lighting without the uncomfortable glare.




PROJECT

DATE


TYPE

QTY

NOTES



LIGHT DISTRIBUTION



*Lumen output measured at 3000k

QUICK SPECS

Size	4"
Watts (W)	14
Delivered lumens*	1430
CRI	90
Voltage (v)	120
Beam angle (deg)	125
Cut hole size (in)	4-1/4"
FT rating	FT6
UGR	13.1
Binning	3 SDCM
LED model	SMD 3030
Color temperature	2700K/3000K/3500K/4000K/5000K
Certifications	ETL, FCC, ICES, JA8/T24, ES, IC, ASTM E283-04

ELECTRICAL DETAILS

Environment	Wet
Location	Indoor/Outdoor
Operating temp. (° C)	-20 to 40
IP rating	IP44
Input voltage (V)	108-135
Output voltage (V)	30-42
Output current (mA)	385
Power factor (%)	98
Driver type	Constant current
THD	12%
Lifespan (hrs)	50 000

ORDERING GUIDE

DDP4-CC

-

Voltage

-

Finish

BLANK - 120v, TRIAC

WH - White



V - 120-277-347V, 0-10v

CONSTRUCTION

Lens material	Acrylic
Optic type	Frosted
Finish type	Matte
Housing material	Aluminum

WHAT'S IN THE BOX

LED recessed fixture
Junction box
3x Push-in wire connectors
Non-Metallic Connector 1/2in
Instruction sheet

ACCESSORIES

REC-RFP-4
Rough-in plate
REC-RFPE4
Rough-in plate
RFP-UNI
Rough-in plate
DDP4-TRIM-BK
Black trim

ADAPTORS

REC-CC-EXT8FT
96" extension cord for recessed fixtures
REC-CC-EXT20FT
240" extension cord for recessed fixtures

RECOMMENDED DIMMER LIST*

BRAND	MODEL	DIMMER SPECS	DIMMING RANGE %		MAX LOAD (units)
			MIN	MAX	
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	5	100	17
Lutron	STCL-153PH-WH-C*	Triac, 150 W Dimmable CFL/LED	0	100	10
Lutron	DVLV-600P-BL	Magnetic Low Voltage, 450W	4	100	30
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	8	100	20
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	3	100	17
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	0	100	10
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	2	100	17
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	0	100	17
Leviton†	6672-1LW	Triac, 150W Dimmable CFL/LED	10	100	10
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	8	100	10
Leviton	PL06-10Z*	Triac, 150 W Dimmable CFL/LED	6	100	10
Leviton	DSL06-1LZ*	Triac, 300 W Dimmable CFL/LED	6	100	20
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	8	100	20
Legrand	ADTP703TUM4*	Triac,450W Dimmable CFL/LED	0	100	30
Legrand	ADPD453LM2*	Triac,450W Dimmable CFL/LED	5	100	30
Legrand	RHL373PW*	Triac, 250W LED	1	100	17
Control 4	C4-APD120-WH	ELV, 120W LED	0	100	8
Control 4	C4-FPD120-WH	Triac, 200W LED	0	100	13
Commercial Electric	HPDA311CWB*	Triac, 150W LED & CFL	0	100	10
TP-Link	HS220*	Triac, 150 W, Dimmable LED (MLV)	2	100	10

*With Low-End Adjustment Feature
Minimal buzzing noise may occur with some dimmers

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DAL'S customer service call 1-877-430-1818 or send an e-mail to info@dals.com.