

NOTCH

The Notch series of regressed downlights is characterized by a deep-set LED position which greatly reduces glare, neatly packaged in a price-conscious solution to general lighting.



2700k

3000k

3500k

4000k

5000k

COLOR SELECT

WET

LOW-GLARE

AIR TIGHT

IC

RATED

T24

JA8

CERTIFIED

Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
DRR2-CC	2"	9 W	500 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
DRR4-CC	4"	11 W	1000 lm			or
DRR6-CC	6"	14 W	1300 lm			V: 120 / 277 / 347V 0-10V dimming (Check for availability)

DRR2-CC

Ø2-3/4"



1-7/8"

Ø3-1/8"

DRR4-CC

Ø4-1/4"




1-13/16"

Ø4-3/4"

DRR6-CC

Ø6-1/2"



1-13/16"

Ø6-7/8"

**Specifications**

Every fixture includes a junction box with an integrated driver

Can be daisy chained

Smooth 360° wide spread

100° beam angle

Frosted lens

Edge lit technology

Switch-selectable CCT

5-year warranty

Finish

● **BK** Black

○ **WH** White

Accessories**RFP-23**

Rough-in plate (DRR2)

RFP-46

Rough-in plate (DRR4, DRR6)

RFP-UNI

Universal rough-in plate (DRR4, DRR6)

DRR4-TRIM-BK

4" recessed panel trim in black

DRR6-TRIM-BK

6" recessed panel trim in black

DRR6-TRIM-SBA

6" recessed panel trim in sandblasted aluminum

REC-CC-EXT8FT

8-foot extension cable

REC-CC-EXT20FT

20-foot extension cable

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.