


SOL

This durable, fully sealed 12V LED recessed ground light features an integrated LED module that provides cool, natural, or warm white light, all adjustable via a 5CCT switch. It is ideal for uplighting, wall washing, pathways, garden accents, and architectural highlights.



IP67
RATED




GRD2-CC



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
GRD2-CC	2"	9 W	600 lm	80	2200, 2700, 3000, 3500, 4000 K	12 VAC



GRD2-CC



Specifications

- Switch-selectable CCT
- IP67-rated products are dustproof and can withstand immersion in water up to 1 meter for 30 minutes
- Can be recessed or surface mounted
- Includes a mounting housing
- 30° beam angle
- 5-year warranty

Finish

- **BK** Black

Power supplies

- LTRP-60-BK**
60W, 120VAC 60Hz input
12VAC output low-voltage transformer

- LTR-300-BK**
300W, 120VAC 60Hz input
12/13/14/15VAC output low-voltage transformer

Note

Low-voltage transformer required.
Sold separately.
Other color temperatures and finish options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALs representative for more information.

Accessories

- LCBL-50-16**
50 feet of 16 gauge low-voltage wiring
- LCBL-100-16**
100 feet of 16 gauge low-voltage wiring
- LCBL-50-14**
50 feet of 14 gauge low-voltage wiring
- LCBL-100-14**
100 feet of 14 gauge low-voltage wiring
- LCBL-100-12**
100 feet of 12 gauge low-voltage wiring
- LCBL-200-12**
200 feet of 12 gauge low-voltage wiring