SLIM SPOT

2200k 2700k 3000k 3500k 4000k

COLOR TEMPERATUR

Illuminate your outdoor landscape with precision using this 12V spotlight, featuring a narrow 10° beam angle for focused and impactful lighting.










Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
LSS10-CC	5-1/2"	10 W	370 lm	80	2200, 2700, 3000,	12 VAC
					3500 4000 K	

LSS10-CC









Specifications

180° swiveling head Ground stake included 10° beam angle Switch-selectable CCT 5-year warranty

Note

Low-voltage transformer required. Sold separately.

Other color temperatures and finish options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.

Finish



Power supplies

LTRP-60-BK

60W, 120VAC 60Hz input 12VAC output low-voltage transformer

LTR-300-BK

300W, 120VAC 60Hz input 12/13/14/15VAC output low-voltage transformer

Accessories

LAN-ACC-MS

6-3/4" metal ground stake

LSP-EXT04

4" extension arm

LSP-WM

Spotlight wall mount adapters

LCBL-50-16

50 feet of 16 gauge low-voltage wiring

LCBL-100-16

100 feet of 16 gauge low-voltage wiring

LCBL-50-14

50 feet of 14 gauge low-voltage wiring

LCBL-100-14

100 feet of 14 gauge low-voltage wiring

LCBL-100-12

100 feet of 12 gauge low-voltage wiring

LCBL-200-12

200 feet of 12 gauge low-voltage wiring