

MSLWALL-CC PINPOINT WALL

LED Wall Mount

MODEL


NAME


From classic to modern exteriors to residential or commercial interiors, this sconce is a must see. With its up/ down light and less than four inch profile, this is discretion at its finest without compromising on performance.



Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124th Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com **dals.com**


PROJECT:	TYPE:
DATE:	QTY:
NOTES:	





QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	LIGHT DIRECTION	FINISH
18"	15W	760lm	2700K	90	120V	30°	Up and down	Black
			3000K					
			3500K					
			4000K					
*Lumen o	output measured at	t 3000K	5000K					



Type of LED SMD	Finish type Powder coated	Lens Half frosted		
Mounting Octo Jbox	Housing material Aluminum	Lens material Plastic		
IP rating IP65	Lifespan 50,000 hrs.	Location Indoor/outdoor	RATINGS	
Operating temperature -20° to 50° C	Certifications ETL, FCC, ICES, ADA	Environment Wet		
	ADAPTERS		ACCESSORIES	
	-		-	
IP65 Operating temperature	50,000 hrs. Certifications ETL, FCC, ICES, ADA ADAPTERS	Indoor/outdoor Environment		



WHAT'S IN THE BOX LED wall mount Mounting bracket Mounting hardware

Wire nuts Instruction sheet

dals		Canada 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1	U.S.A. 4383, NW 124 th Coral Springs, F		877.430.1818 info@dals.com dals.com	ļļ
ELECTRICAL DETAILS	Input voltage 108-132v	Output current 350mA	Power factor 99%	Driver ty Constant	•	
	Output voltage 27-42v	LED model # 3535	THD harmonic distortion <30%	Binning 1 3 SCDM	Binning type 3 SCDM	
FEATURES	Integrated dimmable driver Unique up/down lighting output	Fully sealed light engine Switch-selectable CCT: 2700K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	Superior color consistency			
WARRANTY	covers repairs or replace optics, and electronics. To	ranty from the date of purchas ment of defective parts of the o contact DALS customer serv n e-mail to <u>info@dals.com</u> .	housing,			

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING I MIN	RANGE (%) MAX	MAX LOAD
Lutron	DVCL-153PR-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	10	100	10
Lutron	CTCL-153PDH-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	10	100	10
Lutron	DVWCL-153PH-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	10	100	10
Lutron	MACL-153MRHW-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	1	100	10
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	12	96	20
Leviton	6672-1LW	Triac, 150W Dimmable CFL/LED	Compatible	32	100	10
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	2	100	16
Leviton	DSM10	Triac, 450W Dimmable CFL/LED	Compatible	28	100	30
Legrand	RHCL453PNICCV4	Triac, 450W Dimmable CFL/LED	Compatible	12	100	30
Legrand	ADTP703TUM4	Triac,450W Dimmable CFL/LED	Compatible	21	95	30
Legrand	ADPD453LM2	Triac,450W Dimmable CFL/LED	Compatible	37	100	30
Leviton	6674	Triac, 150 W Dimmable CFL/LED	Compatible	13	100	10
Leviton	IPL06-10Z	Triac, 150 W Dimmable CFL/LED	Compatible	20	100	10
Leviton	DSL06-752	Triac, 150 W Dimmable CFL/LED	Compatible	20	100	10
Lutron	Caseta PD-6WCL-WH-R-C	Triac, 300W Dimmable CFL/LED	Compatible	3	100	20
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	5	100	16
Lutron	Caseta	Triac, LED—up to 250 W	Compatible	1	100	16
Leviton	D26HD-742-1RW	Triac, 300W LED/CFL	Compatible	16	100	20
Dals	SM-DIMSW Smart Dimmer	Triac, 250W LED/CFL	Compatible	10	100	16
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0	100	8
Control 4	C4-FPD120-WH	Triac, 200W LED	Compatible	0	100	13
Legrand	RHL373PW	Triac, 250W LED	Compatible	12	100	16

 * Minimal buzzing noise may occur with some dimmers