

# MODEL **LWJ08-CC** NAME **PROFILE**

## 8" LED Wall Mount


This will not only give you up and down lighting but also central through a delicate acrylic opening. Want to adapt your lighting to your environment? No problem. This wall mount has five color temperatures to choose from which makes it ideal for city or country living.






**Canada** 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124<sup>th</sup> Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com **dals.com** 

PROJECT:	TYPE:
DATE:	QTY:
NOTES:	



#### QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	LIGHT DIRECTION	FINISH
1o"	10W	390lm	2700K 3000K	90	120V	120°	Up, down, and center	Black
			3500K					
*1		4000K						
*Lumen o	output measured a	t 3000K	5000K					



CONSTRUCTION	<b>Lens</b>	<b>Finish type</b>	Type of LED
	Frosted	Powder coated	SMD
	<b>Lens material</b>	Housing material	<b>Mounting</b>
	Glass & plastic	Aluminum	Octo Jbox
RATINGS	<b>Location</b>	<b>Lifespan</b>	IP rating
	Indoor/outdoor	50,000 hrs.	IP65
	<b>Environment</b> Wet	<b>Certifications</b> ETL, FCC, ICES, ADA	<b>Operating</b> temperature -20° to 50° C
ACCESSORIES		ADAPTERS	
-		-	

#### WHAT'S IN THE BOX

LED wall fixture Mounting bracket Mounting hardware Wire nuts Instruction sheet

dals		<b>Canada</b> 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1		<sup>th</sup> Ave., , Florida 33065	877.430.1818 info@dals.com <b>dals.com</b>	ļ
ELECTRICAL DETAILS	<b>Input voltage</b> 108-120v	Output current 230mA	<b>Power factor</b> 98%	<b>Driver ty</b> Constant	•	
	Output voltageLED model #30-42v2835		THD harmonic distortion <30%	Binning 1 3 SCDM	<b>Binning type</b> 3 SCDM	
FEATURES	Integrated dimmable driver Unique up, down, and center lighting output	Fully sealed light engine Switch-selectable CCT: 2700K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	Superior color consistency			
WARRANTY	covers repairs or replac	rranty from the date of purchas ement of defective parts of the To contact DALS customer serv	housing,			

1-877-430-1818 or send an e-mail to info@dals.com.

### **RECOMMENDED DIMMER LIST\***

BRAND	MODEL #	DIMMER SPECS	GRADE		RANGE (%) MAX	MAX LOAD
Dals	SM-DIMSW Smart Dimmer	Triac, 250W LED/CFL	Compatible	6	100	25
Lutron	DVCL-153PR-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	3	100	15
Lutron	CTCL-153PDH-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	6	100	15
Lutron	STCL-153PH-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	1	100	15
Lutron	DVWCL-153PH-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	6	100	15
Lutron	MACL-153MRHW-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	1	100	15
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	6	93	30
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	1	100	25
Lutron	Caseta PD-6WCL-WH-R-C	Triac, 150W Dimmable CFL/LED	Compatible	1	100	15
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	2	100	25
Lutron	Caseta	Triac, LED—up to 250 W	Compatible	1	100	25
Leviton	6672-1LW	Triac, 150W Dimmable CFL/LED	Compatible	21	100	15
Leviton	DSM10	Triac, 450W Dimmable CFL/LED	Compatible	17	100	45
Leviton	6674	Triac, 150 W Dimmable CFL/LED	Compatible	9	100	15
Leviton		Triac, 150 W Dimmable CFL/LED	Compatible	15	100	15
Leviton	DSL06-752	Triac, 150 W Dimmable CFL/LED	Compatible	15	100	15
Leviton	D26HD-742-1RW	Triac, 300W LED/CFL	Compatible	9	100	30
Legrand	RHCL453PNICCV4	Triac, 450W Dimmable CFL/LED	Compatible	8	100	45
Legrand	ADTP703TUM4	Triac,450W Dimmable CFL/LED	Compatible	10	93	45
Legrand	RHL373PW	Triac, 250W LED	Compatible	5	100	25
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0	100	12
Control 4	C4-FPD120-WH	Triac, 200W LED	Compatible	0	100	20