

MODEL LWJ24-CC NAME PROFILE

24" LED Wall Mount

This will not only give you up and down lighting but also central through a delicate acrylic opening. Want to adapt your lighting to your environment? No problem. This wall mount has five color temperatures to choose from which makes it ideal for city or country living.






Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124th Ave., Coral Springs, Florida 33065


877.430.1818 info@dals.com **dals.com**

PROJECT:	TYPE:
DATE:	QTY:
NOTES:	



QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	LIGHT DIRECTION	FINISH
24"	45W	2345lm	2700K 3000K 3500K	90	120V	120°	Up, down, and center	Black
*Lumen d	output measured a	t 3000K	4000K 5000K					



CONSTRUCTION	Lens Frosted	Finish type Powder coated	Type of LED SMD
	Lens material Glass & plastic	Housing material Aluminum	Mounting Octo Jbox
RATINGS	Location Indoor/outdoor	Lifespan 50,000 hrs.	IP rating IP65
	Environment Wet	Certifications ETL, FCC, ICES, ADA	Operating temperature -20° to 50° C
ACCESSORIES		ADAPTERS	
-		-	

WHAT'S IN THE BOX

LED wall fixture Mounting bracket Mounting hardware Wire nuts Instruction sheet

dals		Canada 80, de la Seigneurie blvd., E Blainville, Quebec J7C 4N1		th Ave., , Florida 33065	877.430.1818 info@dals.com dals.com	ļ
ELECTRICAL DETAILS	Input voltage 120v	Output current 1000mA	Power factor 100%	Driver ty Constant	•	
	Output voltage 24-45v	LED model # 2835	THD harmonic distortion <30%	Binning t 3 SCDM	ууре	
FEATURES	Integrated dimmable driver Unique up, down, and center lighting output	Fully sealed light engine Switch-selectable CCT: 2700K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	Superior color consistency			
WARRANTY	covers repairs or replac	nranty from the date of purchas ement of defective parts of the To contact DALS customer serv	housing,			

1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING RANGE (%) MIN MAX	MAX LOAD
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	Compatible	3 100	6
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	3 100	3
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	3 100	3
Lutron	STCL-153PH-WH-C*	Triac, 150 W Dimmable CFL/LED	Compatible	1 100	3
Lutron	DVWCL-153PH-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	3 100	3
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	Compatible	1 100	3
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	3 100	7
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	Compatible	4 100	6
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	Compatible	1 100	7
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	Compatible	4 100	6
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	Compatible	1 100	6
Leviton	DSM10-1LZ*	Triac, 450W Dimmable CFL/LED	Compatible	3 100	10
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	Compatible	3 100	3
Leviton	DSL06-1LZ*	Triac, 150 W Dimmable CFL/LED	Compatible	3 100	3
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	Compatible	5 100	7
Legrand	RHCL453PNICCV4*	Triac, 450W Dimmable CFL/LED	Compatible	10 100	10
Legrand	ADPD453LM2*	Triac,450W Dimmable CFL/LED	Compatible	8 100	10
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0 100	3
Control 4	C4-FPD120-WH	Triac, 200W LED	Compatible	0 100	4

* With Low-End Adjustment Feature

* Minimal buzzing noise may occur with some dimmers