DUO-PUCK










These robust LED pucks, equipped with a frosted lens, deliver highly efficient punches of white light, making them well-suited for under-cabinet lighting and various other applications.





Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
4005-CC	Ø2.625"	2 W	138 lm	80	2700 K/ 3000 K/ 3500 K/	12 V
*Per fixture					4000 K/ 5000 K	
K4005-CC	Ø2.625"	2 W*	138 lm*			

Specifications

12V DC LED driver required

12" input lead with guick connector

24" interconnection harness included

Can be recessed or surface mounted

Switch-selectable CCT

Smooth 360° wide spread

Kits available

5-year warranty

Power supplies: plug-in

ETR-LED10WPI

12V DC/10W class 2 LED driver

ETR-LED24WPI

12V DC/24W class 2 LED driver

Power supplies: hard-wired

DD1260

LED driver and dimmer in one unit

BT06DIM-IC

6W dimmable LED hardwire driver

BT12DIM-IC

12W dimmable LED hardwire driver

BT24DIM-IC

24W dimmable LED hardwire driver

BT36DIM

36W dimmable LED hardwire driver

BT48DIM

48W dimmable LED hardwire driver

Finish



BK Black



SN Satin Nickel



WH White

Accessories

4000-E24

24" extension cord

4000-E60

60" extension cord

4000HRNS-24

24" interconnection harness

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.