


# POWERLED LINEAR




Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.




**6009CC**




**6012CC**




**6024CC**



**6036CC**



**6048CC**



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
<b>6009CC</b>	9"	3 W	250 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
<b>6012CC</b>	12"	4 W	330 lm			
<b>6024CC</b>	24"	8 W	675 lm			
<b>6036CC</b>	36"	12 W	1080 lm			
<b>6048CC</b>	48"	16 W	1300 lm			

## Specifications

- Switch-selectable CCT
- Dimmable with regular low-voltage electronic dimmers
- Smooth linear wide spread
- Multiple fixtures can be linked together (up to 200W)
- 5-year warranty

## Finish

- SBA** Sandblasted aluminum

## Note

Junction box model 6000-JB or power cord model 6000-ACCPC are required for installation. Sold separately.

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALs representative for more information.

## Accessories

- 6000-ACCE06**  
6" extension cord
- 6000-ACCE24**  
24" extension cord
- 6000-ACCE60**  
60" extension cord
- 6000-ACCLR**  
Kit of left and right L connectors
- 6000-ACCPC**  
6' power cord
- 6000-JB**  
Junction box