COLUMN

2200k 2700k 3000k 3500k 4000k

COLOR TEMPERATUR




The Column series, a robust rectangular bollard that features a minimalist design for the ultimate in urban sophistication. Constructed of solid aluminum, it provides a chic solution to eco-conscious homeowners.




Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
LRB20-CC	20"	12 W	600 lm	80	2200, 2700, 3000,	12 VAC
LRB30-CC	30"	13 W	700 lm		3500, 4000 K	

LRB20-CC



LRB30-CC





Specifications

Ground stake included

108° beam angle

Can be mounted to wood or concrete using the included mounting bracket (screws not included)

Switch-selectable CCT

5-year warranty

Finish



BK Black

Power supplies

LTRP-60-BK

60W, 120VAC 60Hz input 12VAC output low-voltage transformer

LTR-300-BK

300W, 120VAC 60Hz input 12/13/14/15VAC output low-voltage transformer

Note

Low-voltage transformer required. Sold separately.

Other color temperatures and finish options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.

Accessories

LCBL-50-16

50 feet of 16 gauge low-voltage wiring

LCBL-100-16

100 feet of 16 gauge low-voltage wiring

LCBL-50-14

50 feet of 14 gauge low-voltage wiring

LCBL-100-14

100 feet of 14 gauge low-voltage wiring

LCBL-100-12

100 feet of 12 gauge low-voltage wiring

LCBL-200-12

200 feet of 12 gauge low-voltage wiring