

MODEL RTJB4-CC NAME ALTER 4-Inch Recessed Retrofit

Our LED retrofit panels provide the perfect solution for your renovations. There's no need to completely change your current lighting, simply use these innovative products and retrofit your existing installation.






Canada 80, de la Seigneurie blvd., E. Blainville, Quebec J7C 4N1 **U.S.A.** 4383, NW 124th Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com **dals.com**


PROJECT:	ТҮРЕ:
DATE:	QTY:
NOTES:	
NOTES.	

00 Ø4-3/4"



QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 5CCT	CRI	VOLTAGE	BEAM ANGLE	FINISH
4"	9W	565lm	2700K	90	120V	149°	O White
			3000K				U U
			3500K				
			4000K				
*Lumen outp	ut measured at 3000k	<	5000K				



CONSTRUCTION	Lens Frosted	Type of optics Flat lens	Type of LED SMD
	Lens material Plastic	Housing material Cast aluminum	Cut hole size 4" or Octo Jbox
RATINGS	Placement Indoor/Outdoor	Lifespan 50,000 hrs.	FT rating -
	Location Wet	Certifications ETL, FCC, ICES, ES IC, ASTM E283-04, T24	Operating temperature -20° to 40° C
ACCESSORIES		ADAPTERS	
RTJB4-ACC 4'' Can Kit - Clips and E26 Socket			

RTJB4-TRIM-BK Recessed Panel Trim

<u>SM-DIMSW</u> Smart Dimmer Switch

WHAT'S IN THE BOX LED recessed fixture Mounting hardware Instruction sheet

dals		Canada 80, de la Seigneurie blvd., Blainville, Quebec J7C 4N1	E.	U.S.A. 4383, NW 124 th Av Coral Springs, Flo		877.430.1818 info@dals.com dals.com	ψ
ELECTRICAL DETAILS	Input voltage 108-132V	Output current 520mA	Powe 90%	er factor	Driver ty Constant	•	
	Output voltage 115V	LED model # 2835	disto	THD harmonic distortion <30%		Binning type 3 SDCM	
FEATURES	Integrated driver Superior LED performance and	Fits into 4" recessed housings (accessories sold separetely)	when	rated alternative mounted onto a ated junction box		electable CCT: 000 K/ 3500 K/ 5000 K	
	lifespan	Fits on octagonal junction boxes	Magn	etic trim finish			
WARRANTY	covers repairs or repla	varranty from the date of purchate acement of defective parts of the	e housir	ng,			

covers repairs or replacement of defective parts of the housing optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE		RANGE (%) MAX	MAX LOAD
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	0	62	33
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	0	88	28
Lutron	Caseta PD-10NXD-WH	Triac, LED—up to 250 W	Compatible	0	89	28
Leviton	6672-1LW	Triac, 150W Dimmable CFL/LED	Compatible	0	94	17
Leviton	D26HD-742-1RW	Triac, 300W LED/CFL	Compatible	0	100	33
Legrand	RHCL453PNICCV4	Triac, 450W Dimmable CFL/LED	Compatible	0	99	50
Legrand	ADTP703TUM4	Triac,450W Dimmable CFL/LED	Compatible	0	73	50
Legrand	ADPD453LM2	Triac,450W Dimmable CFL/LED	Compatible	0	100	50
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0	100	13

 * Minimal buzzing noise may occur with some dimmers