
DELTA

Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. With 5 sizes to choose from, every application is covered.





















DELTA

Our LED flush mounts incorporate edge-lit technology, eliminating hot spots and glare. With 5 sizes to choose from, every application is covered.





COLOR TEMPERATURE






T24 JA8 CERTIFIED


Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options 🖟
CFLEDR06-CC	6"	11 W	700 lm	90	2700, 3000, 3500, 4000, 5000 К	120 V TRIAC dimming
CFLEDSQ06-CC*	6"	11 W	700 lm			
CFLEDR10-CC	10"	17 W	1200 lm			or
CFLEDSQ10-CC*	10"	17 W	1200 lm			V: 120/277/347V 0-10V dimming (Check for availability)
CFLEDR14-CC	14"	26 W	1700 lm			
CFLEDSQ14-CC*	14"	26 W	1700 lm			
CFLEDR18-CC	18"	30 W	2100 lm			
CFLEDR24-CC	24"	40 W	3000 lm			

^{*}Not available in multi-voltage


CFLEDR06-CC




CFLEDR10-CC




CFLEDR14-CC



CFLEDR18-CC




CFLEDR24-CC




CFLEDSQ06-CC



CFLEDSQ10-CC



CFLEDSQ14-CC



Specifications

Integrated dimmable driver Smooth 360° wide spread Minimal heat emission Frosted lens Edge-lit technology Cast aluminum construction Suitable for outdoor locations on covered ceilings only 5-year warranty

Finish

BK Black **GD** Gold
(6, 10, 14" rd

(6, 10, 14" round models)

SN Satin Nickel
(6, 10, 14" round and square models)

WH White

Multi-voltage(V) №

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALS representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.