


HORIZON

Made of high strength aluminum alloy with adjustable precision. Incredibly bright with a 120° degree beam angle, it can be wall mounted or staked in the ground.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
DCP-FLD30	7"	30 W	3000 lm	80	RGB + 2200 K - 4000 K	24 V DC

DCP-FLD30



Specifications

Full color spectrum
2200K - 4000K in pure whites
Can be wall mounted
120° beam angle
Dimmable through the Dals Connect app and the Clicc remote (DCP-RMCT)
5-year warranty

Note

Add the DALS Connect Pro Core transformer for even greater flexibility: voice control, remote access, expanded mesh network.

Finish

● **BK** Black

Smart transformers

DCP-TR60-BK

60W, 120VAC 60Hz input, 24V DC output low-voltage smart transformer

DCP-TR200-BK

200W, 120VAC 60Hz input, 24V DC output low-voltage smart transformer

DCP-TR300-BK

300W, 120VAC 60Hz input, 24V DC output low-voltage smart transformer

Download the Dals Connect app

Create groups
Set schedules
Remote access*
Compatible with Google Assistant and Amazon Alexa*



* Core needed

Accessories

DCP-RMCT

Smart remote

DCP-PTR36

Plug-in driver

DCP-ACC-MS12

12" metal ground stake

DCP-ACC-MS06

6" metal ground stake

DCP-ACC-MB

Mounting bracket

LCBL-50-16, LCBL-100-16

50 or 100 feet of 16-gauge low-voltage wiring

LCBL-50-14, LCBL-100-14

50 or 100 feet of 14-gauge low-voltage wiring

LCBL-100-12, LCBL-200-12

100 or 200 feet of 12-gauge low-voltage wiring