# **FUSION**

The Fusion is a slim gimbal recessed panel with 5CCT, offering advanced lighting flexibility for precise illumination. Its gimbal design allows users to direct light as needed, and the 5CCT feature provides color temperature versatility, making the Fusion an ideal choice for both residential and commercial applications.



	1-1/2"
Ç	04-15/16"
GPN6-CC	Ø6-1/4"
	1
	1-3/4"
	Ø7"

Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options 🖡
GPN4-CC	4"	10 W	850 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
GPN6-CC	6"	13 W	1050 lm		4000, 3000 K	or

V: 120/277/347V 0-10V dimming (Check for availability)

0 0 0 0 0 2700k 3000k 3500k 4000k 5000k

COLOR TEMPERATURE

WET

<u>\_25°</u>

#### Specifications

Every fixture includes a junction box with an integrated driver Switch-selectable CCT 110° beam angle 25° tilting, 360° rotation Cast aluminum construction 5-year warranty

#### Finish

**BK** Black ○ WH White

### Accessories

**RFP-UNI** Universal rough-in plate RFP-46

Rough-in plate for 4" and 6" models **GPN-CC-EXT8FT** 

8-foot extension cable

GPN-CC-EXT20FT 20-foot extension cable



## Multi-voltage (V) 🖡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALS representative for additional information and to confirm availability.

### Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.