

HILUX

Dals' high-powered recessed downlight is a go-to for your commercial projects. With its five color temperatures to choose from, a cast aluminum housing, high lumen output, and indoor/outdoor rating, this can be installed just about anywhere. From clinics to schools and hotels to boutiques, this is the only recessed fixture you will need.



COLOR TEMPERATURE

- WET
- LOW-GLARE
- AIR TIGHT
- IC**
RATED
- T24**
JA8
CERTIFIED
- Intertek

HPD4-CC



HPD6-CC



HPD8-CC



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
HPD4-CC	4"	20 W	1415 lm	90	2700, 3000, 3500, 4000, 5000 K	120V TRIAC dimming
HPD6-CC	6"	30 W	2100 lm			or
HPD8-CC	8"	40 W	2600 lm			V: 120 / 277 / 347V 0-10V dimming (Check for availability)

HPD4-CC

Ø4-1/4"



2-1/8"

Ø5"

HPD6-CC

Ø6-1/2"



2-1/2"

Ø7-1/4"

HPD8-CC

Ø7-1/2"



2-1/2"

Ø8-3/4"



Specifications

Every fixture includes a junction box with an integrated driver
 Switch-selectable CCT
 Smooth 360° wide spread
 90° beam angle
 Cast aluminum construction
 5-year warranty

Finish

- BK** Black (HPD4 and HPD6 only)
- WH** White

Accessories

- RFP-46**
Rough-in plate for HPD4, HPD6
- RFP-58**
Rough-in plate for HPD8
- RFP-UNI**
Universal rough-in plate
- REC-CC-EXT8FT**
8-foot extension cable
- REC-CC-EXT20FT**
20-foot extension cable

Multi-voltage (V) ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALs representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALs representative for more information.