Horus

A versatile lighting solution with a flexible design for precise illumination, its gimbal mechanism allows users to easily adjust the light angle, making it ideal for residential or commercial settings. The compact 3-inch size is suitable for tight spaces, and the spotlight's focused beam makes it perfect for accent lighting or task-oriented applications.









Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage	
GSP3-CC	3"	12 W	950 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V	
Specifications		Finish	Finish		Note		
Every fixture includes a junction box with an integrated driver Over 50,000 hours service life Switch-selectable CCT: 2700 K/3000 K/ 3500 K/4000 K/5000 K		GD	 BK Black GD Gold WH White 		voltage options are av require minimum order and longer lead times.	Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.	
60° beam angle 30° tilting, 360° rotation Cast aluminum construction Suitable for damp locations Refer to website for dimmer compatibility IC certification (suitable for direct contact with insulation)		Accessories RFP-23 Rough-in plate					
		GSP-CC-EXT8FT 8-foot extension cable GSP-CC-EXT20FT 20-foot extension cable					
Air-tight certified of 5-year warranty	as per ASTM E283-04						



Ø 3-3/8"



