

# Excel

LED panel lights are more accessible than ever before. Their sleek and minimal construction, combined with a two-hour fire-rated housing, offers a blend of security and modern clean design.

NEW

WET

ENERGY STAR

AIR TIGHT

ETL Intertek

IC RATED

2700k 3000k 3500k 4000k 5000k

COLOR TEMPERATURE

WARM DIMMING\*

FIRE RATED\*\*



\*Model 5004-DW only

\*\*Models 5004-FR-CC, 5006-FR-CC only

Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
<b>5004-DW*</b>	4"	11 W	850 lm	80	3000 K - 2200 K	120 V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
<b>5004-FR-CC**</b>	4"	11 W	825 lm		2700, 3000, 3500, 4000, 5000 K		
<b>5006-FR-CC**</b>	6"	14 W	1230 lm				

\*Dim-to-warm technology dims from 3000 K to 2200 K

\*\*2-hour fire-rated without additional housing or hardware, in accordance with UL 263, ASTM E119, and CAN ULC S101

### Specifications

Every fixture includes a junction box with an integrated driver  
 Over 35,000 hours of service life  
 Can be daisy chained  
 Superior LED performance and lifespan  
 Smooth 360° wide spread  
 Minimal heat emission  
 Frosted lens  
 Edge lit technology  
 Aluminum construction  
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K  
 Very low profile  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature: -20° to 40° C  
 5-year warranty

### Finish

○ **WH** White

### Accessories

**REC-TRIM4-BK (5004-DW only)**

4" recessed panel trim in black

**REC-TRIM4-GD (5004-DW only)**

4" recessed panel trim in gold

**REC-TRIM4-SN (5004-DW only)**

4" recessed panel trim in satin nickel

**REC-3K-EXT8FT (5004-DW only)**

8-foot extension cable

**REC-3K-EXT20FT (5004-DW only)**

20-foot extension cable

**REC-CC-EXT8FT (5004/6-FR only)**

8-foot extension cable

**REC-CC-EXT20FT (5004/6-FR only)**

20-foot extension cable

**RFP-46 (5004, 5006)**

Rough-in plate

**RFP-UNI (5004, 5006)**

Universal rough-in plate

### Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

### Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

