Access

LED panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations.









Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
2003	3"	6 W	400 lm	80	3000 K	120 V
2004	4"	9 W	600 lm			
2006	6"	11 W	800 lm			

Specifications

Every fixture includes a junction box with an integrated driver Over 35,000 hours of service life Can be daisy chained Superior LED performance and lifespan Smooth 360° wide spread Minimal heat emission Frosted lens Edge lit technology Aluminum construction Very low profile IC certification (suitable for direct contact with insulation) Air-tight certified as per ASTM E283-04 Suitable for damp locations Refer to website for dimmer compatibility 5-year warranty

Finish

○ WH White

Accessories

REC-TRIM4-BK (2004) 4" recessed panel trim in black

REC-TRIM4-GD (2004) 4" recessed panel trim in gold

REC-TRIM4-SN (2004) 4" recessed panel trim in satin nickel

REC-TRIM6-BK (2006) 6" recessed panel trim in black

REC-TRIM6-GD (2006) 6" recessed panel trim in gold

REC-TRIM6-SN (2006) 6" recessed panel trim in satin nickel

2000-EXT8FT 8-foot extension cable

2000-EXT20FT 20-foot extension cable

RFP-23 (2003) Rough-in plate

RFP-46 (2004, 2006) Rough-in plate

RFP-UNI (2004, 2006) Universal rough-in plate

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALS representative for more information.



4-1/8" x 2-1/2" x 1-3/8"

Ø3-3/4"



