

DELTA

CFLEDR24-CC

24" round flush mount

dals


PROJECT

DATE


TYPE

QTY

NOTES



LIGHT DISTRIBUTION



Distance from luminaire	FC at Nadir	Diameter
4'	62.4 fc	12'-10"
6'	27.7 fc	19'-3"
8'	15.6 fc	25'-8"
10'	10.0 fc	32'-1"
12'	6.9 fc	38'-6"

*measured at 3000k

SPECS

Watts (W)	40
Delivered lumens*	3000
Voltage (v)	120
CRI	92
TM-30	Rf: 91 Rg: 102
Binning	3 SDCM
Beam angle (deg)	110
UGR	40
LED model	SMD 2835
Light direction	Down
Dimming	Triac / ELV
Mounting	Twist bracket
Color temperature	2700K/3000K/3500K/4000K/5000K

CONSTRUCTION

Lens material	Polycarbonate
Optic type	Frosted

ELECTRICAL DETAILS

Location	Wet - covered ceiling
Environment	Indoor/Outdoor
Operating temp. (° C)	-20 to 40
IP rating	IP44
Input voltage (V)	108-120
Input current (mA)	357
Output voltage (V)	-
Output current (mA)	-
Power factor (%)	96
Driver type	Driver on board
THD	≤ 30%
Lifetime @ L70	>50 000hrs

Finish type	Matte
Housing material	Aluminum

ORDERING GUIDE

CFLEDR24-CC

-

Finish

WH - White

BK - Black



CERTIFICATIONS

ETL listed UL-1598 and CSA C22.2 No. 250.0

Title 24-JA8

Compliant to FCC Title 47 Part 15; Class B

ICES-005 Issue 5



CANADA
80, Blvd. de la Seigneurie E.
Blainville, Quebec J7C 4N1

USA
4383, NW 124th Ave.,
Coral Springs, Florida 33065

1 877.430.1818
info@dals.com
dals.com

WHAT'S IN THE BOX

- LED flush mount fixture
- Mounting bracket
- Mounting hardware
- Wire nuts
- Instruction sheet

ACCESSORIES

ADAPTORS

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DAL'S customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST**

BRAND	MODEL	DIMMER SPECS	DIMMING RANGE %		MAX LOAD (units)
			MIN	MAX	
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	0	100	6
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	0	98	4
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	0	98	4
Lutron	DVLV-600P-BL	Magnetic Low Voltage, 450W	1	100	11
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	0	94	4
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	0	94	6
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	0	93	4
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	0	99	6
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	0	92	6
Leviton†	6672-1LW	Triac, 150W Dimmable CFL/LED	0	100	4
Leviton	DSM10-1LZ*	Triac, 450W Dimmable CFL/LED	0	100	11
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	0	100	4
Leviton	PL06-10Z*	Triac, 150 W Dimmable CFL/LED	0	100	4
Leviton	DSL06-1LZ*	Triac, 150 W Dimmable CFL/LED	0	100	4
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	0	100	8
Legrand	RHCL453PNICCV4*	Triac, 450W Dimmable CFL/LED	0	100	11
Legrand	ADTP703TUM4*	Triac,450W Dimmable CFL/LED	0	100	11
Legrand	ADPD453LM2*	Triac,450W Dimmable CFL/LED	0	100	11
Control 4	C4-APD120-WH	ELV, 120W LED	0	100	3
Control 4	C4-FPD120-WH	Triac, 200W LED	0	100	5
Commercial Electric	HPDA311CWB*	Triac, 150W LED & CFL	0	100	4
TP-Link	HS220*	Triac, 150 W, Dimmable LED (MLV)	0	100	4
Leviton	RDL06-10Z	Triac, 150W LED & CFL	9	100	4

*With low-end adjustment feature. **Some dimmers may produce minimal buzzing noise.





Blainville, Quebec J7C 4N1

Coral Springs, Florida 33065

dals.com