


SOL

This durable, fully sealed 12V LED recessed ground light features an integrated LED module that provides cool, natural, or warm white light, all adjustable via a 5CCT switch. It is ideal for uplighting, wall washing, pathways, garden accents, and architectural highlights.




2200k2700k3000k3500k4000k

COLOR TEMPERATURE



WET

IP67
RATED




Intertek

Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
GRD2-CC	2"	9 W	600 lm	80	2200, 2700, 3000, 3500, 4000 K	12 VAC



GRD2-CC



Specifications

Switch-selectable CCT
 IP67-rated products are dustproof and can withstand immersion in water up to 1 meter for 30 minutes
 Maximum static load: 3,000 lbs
 Impact protection: IK09
 Can be recessed or surface mounted
 Includes a mounting housing
 30° beam angle
 5-year warranty

Finish

● **BK** Black

Power supplies

LTRP-60-BK
 60W, 120VAC 60Hz input
 12VAC output low-voltage transformer

LTR-300-BK
 300W, 120VAC 60Hz input
 12/13/14/15VAC output low-voltage transformer

Note

Low-voltage transformer required.
 Sold separately.
 Other color temperatures and finish options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

Accessories

LCBL-50-16
 50 feet of 16 gauge low-voltage wiring

LCBL-100-16
 100 feet of 16 gauge low-voltage wiring

LCBL-50-14
 50 feet of 14 gauge low-voltage wiring

LCBL-100-14
 100 feet of 14 gauge low-voltage wiring

LCBL-100-12
 100 feet of 12 gauge low-voltage wiring

LCBL-200-12
 200 feet of 12 gauge low-voltage wiring