

NEW

REACH

LED panel lights are more accessible than ever before. The sleek and minimal construction allows for the easiest of installations.



COLOR SELECT



WET



AIR TIGHT



RATED



CERTIFIED



COASTAL RATED*



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage options ⚡
PNL3-CC	3"	7 W	575 lm	92	2700, 3000, 3500, 4000, 5000 K	120V
PNL4-CC	4"	9 W	740 lm	92	2700, 3000, 3500, 4000, 5000 K	120 V TRIAC dimming or V: 120 / 277 / 347V 0-10V dimming
PNL6-CC	6"	12 W	990 lm	92		
PNL4-CC-K12	4"	9 W	740 lm [†]	92	2700, 3000, 3500, 4000, 5000 K	120V
PNL6-CC-K12	6"	12 W	990 lm [†]	92		
PNL4SQ-CC	4"	9 W	740 lm	92	2700, 3000, 3500, 4000, 5000 K	120V

[†]Per fixture


*Designed to withstand salty air. 480h salt spray test approved. Equivalent to 6.5 years in coastal environment.


PNL3-CC Ø3-3/8" 




PNL4-CC Ø4-1/4" 



PNL4SQ-CC Ø4-1/2" 



PNL6-CC Ø6-1/4" 



Specifications

Every fixture includes a junction box with an integrated driver
Can be daisy chained
Superior LED performance and lifespan
Frosted lens
Edge lit technology
Aluminum construction
Designed to withstand salty air
Very low profile
Kits of 12 available
5-year warranty

Finish

- **BK** Black (Available for individual 4" and 6" models only)
- **WH** White

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

Accessories

REC-RFP-13, REC-RFP-DOUBLE23
Rough-in plate for PNL3

REC-RFP-4, REC-RFPE4
Rough-in plate for PNL4

REC-RFP-46SQ
Rough-in plate for PNL4SQ

REC-RFP-6, REC-RFPE6
Rough-in plate for PNL6

RFP-UNI
Universal rough-in plate for PNL3, PNL4, PNL6

PNL4-TRIM-BK, PNL6-TRIM-BK
4" and 6" black recessed panel trims for PNL4-CC, PNL6-CC

PNL-EXT8FT, PNL-EXT20FT
8 ft and 20 ft extension cables for PNL4-CC, PNL6-CC