

MODEL	LEDWALL-B-CC			
NAME	Brooklyn			
	4in Round Wall Sconce			


The key design element of our new LED cylinder is the removable lens. This feature allows for three distinctive styles during installation.




Canada 80, de la Seigneurie blvd., E. Blainville, Quebec j7C 4N1 U.S.A. 4383, NW 124th Ave., Coral Springs, Florida 33065 877.430.1818 info@dals.com dals.com

PROJECT T	YPE
DATE Q	ITY
	·
NOTES	








ELECTRICAL DETAILS

Housing material

Aluminum

LIGHT DISTRIBUTION



*Lumen output measured at 3000k

QUICK SPECS

Size 12" Environment Wet Watts (W) 27 Location Indoor/Outdoor **Delivered lumens*** 1825 Operating temp. (° C) -30 to 40 CRI 90 **IP** rating IP65 Voltage (v) 120 Input voltage (V) 120-277 Output voltage (V) Beam angle (deg) 115 18-40 Output current (mA) 700 Mounting Screwed in 50 000 **Power factor** 90 Lifespan (hrs) Binning 5 SCDM **Driver type** Constant current THD LED model COB ≤ 20% up and downlight Certifications ETL, FCC, ICES, T24/JA8 **Light direction** 2700K/3000K/3500K/4000K/5000K **Color temperature**

 ORDERING GUIDE
 CONSTRUCTION

 LEDWALL-B-CC

 Finish
 Glass

 BK - Black
 Ensitype

 Finish type
 Powder coated

WHAT'S IN THE BOX	ACCESSORIES	ADAPTORS	
LED flush mount fixture			
Mounting bracket			
Mounting hardware			
Wire nuts			
Instruction sheet			

RECOMMENDED DIMMER LIST*

BRAND	MODEL	DIMMER SPECS	GRADE	DIMMING RANGE %		MAX LOAD
				MIN	MAX	MAX LOAD
Lutron	DVELV-300P-WH	ELV 300W	Compatible	6	92	11
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	Compatible	1	100	9
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	Compatible	2	100	9
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	0	100	4

*With Low-End Adjustment Feature

Minimal buzzing noise may occur with some dimmers

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DALS customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

