

PIVOT

FGM4-CDW-TRIO

4" triple flat gimbal recessed

dals


PROJECT

DATE


TYPE

QTY

NOTES



LIGHT DISTRIBUTION



Distance from luminaire	FC at Nadir	Diameter
4'	241.7 fc	2'-9"
6'	107.4 fc	4'-2"
8'	60.4 fc	5'-7"
10'	38.7 fc	6'-11"
12'	26.9 fc	8'-4"

*measured at 3000k

SPECS

Cut hole size (in)	13" x 4-5/8"	
Watts (W)	27	
Delivered lumens*	2780	
Voltage (v)	133	
FT rating	FT6	
CRI	92	
TM-30	Rf : 91	Rg : 100
Binning	3 SDCM	
Beam angle (deg)	40	
UGR	30	
LED model	SMD2835	
Dimming	Triac / ELV	
Color temperature	2700/3000/3500/4000/5000k + DW 3000-2200k	

CONSTRUCTION

Lens material	Polycarbonate
Optic type	Optical lens

ELECTRICAL DETAILS

Location	Wet	
Environment	Indoor/Outdoor	
Operating temp. (° C)	-20	to 40
IP rating	IP65	
Input voltage (V)	120	
Input current (mA)	228	
Output voltage (V)	35	
Output current (mA)	660	
Power factor (%)	99	
Driver type	Constant current	
THD	0.14	
Lifetime @ L70	>50 000hrs	

Finish type	Matte
Housing material	Aluminum

ORDERING GUIDE

FGM4-CDW-TRIO

-

Finish

WH - White



BK - Black



CERTIFICATIONS

ETL listed UL-1598 and CSA C22.2 No. 250.0

Title 24-JA8, Energy Star, IC rated, Air-tight ASTM E283-04

Compliant to FCC Title 47 Part 15; Class B

ICES-005 Issue 5



CANADA
80, Blvd. de la Seigneurie E.
Blainville, Quebec J7C 4N1

USA
4383, NW 124th Ave.,
Coral Springs, Florida 33065

1 877.430.1818
info@dals.com
dals.com

WHAT'S IN THE BOX

Recessed fixture
Junction box
3x push-in wire connectors
1/2" non-Metallic Connector
Instruction sheet

ACCESSORIES

RFP-TRIO
Rough-in template

EXTENSIONS

REC-CDW-EXT8FT
96" extension cord for recessed fixtures

REC-CDW-EXT20FT
240" extension cord for recessed fixtures

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DAL'S customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST**

BRAND	MODEL	DIMMER SPECS	DIMMING RANGE %		MAX LOAD (units)
			MIN	MAX	
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	5	100	10
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	5	100	6
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	5	100	6
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	1	100	6
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	8	100	12
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	1	100	10
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	5	100	6
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	8	100	10
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	1	100	10
Leviton	DSM10-1LZ*	Triac, 450W Dimmable CFL/LED	7	100	18
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	8	100	6
Leviton	PL06-10Z*	Triac, 150 W Dimmable CFL/LED	8	100	6
Leviton	DSL06-1LZ*	Triac, 300 W Dimmable CFL/LED	8	100	12
Leviton	D26HD-742-1RW*	Triac, 300W LED/CFL	11	100	12
Legrand	ADTP703TUM4*	Triac, 450W Dimmable CFL/LED	0	100	18
Control 4	C4-APD120-WH	ELV, 120W LED	0	100	5
Control 4	C4-FPD120-WH	Triac, 200W LED	0	100	8
Commercial Electric	HPDA311CWB*	Triac, 150W LED & CFL	0	100	6
TP-Link	HS220*	Triac, 150 W, Dimmable LED (MLV)	5	100	6

*With low-end adjustment feature. **Some dimmers may produce minimal buzzing noise.

FGM4-CDW-TRIO

Revision 0 | 2026-03



CANADA
80, Blvd. de la Seigneurie E.
Blainville, Quebec J7C 4N1

USA
4383, NW 124th Ave.,
Coral Springs, Florida 33065

1 877.430.1818
info@dals.com
dals.com