

RGR

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

RGR6-CDW



RGR1-CDW




RGR2-CDW



RGR4-CDW



NEW



COLOR SELECT +



COLOR SELECT



UNIVERSAL DRIVER



WET



LOW-GLARE



AIR TIGHT

IC

RATED

T24

JA8

CERTIFIED



Intertek



RGR6SQ-CDW



RGR2SQ-CDW



RGR4SQ-CDW




*ColorSelect+ is available for CDW models only. UNV models feature 5CCT (2700, 3000, 3500, 4000, 5000K)

*Energy Star certification applies to all models except RGR1-CDW

RGR

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.



COLOR SELECT +



COLOR SELECT



UNIVERSAL DRIVER



WET



LOW-GLARE



AIR TIGHT



RATED



CERTIFIED












Intertek



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
RGR1-CDW	1"	6 W	450 lm	92	6 CCT: 2700, 3000, 3500, 4000, 5000K + Dim-to-Warm (3000 - 2200K)	120V
RGR2-CDW	2"	8 W	700 lm	92		
RGR2SQ-CDW	2"	8 W	700 lm	92		
RGR4-CDW	4"	14 W	1180 lm	93		
RGR4SQ-CDW	4"	14 W	1180 lm	93		
RGR6-CDW	6"	20 W	1640 lm	90		
RGR6SQ-CDW	6"	20 W	1640 lm	90		
RGR2HP-CC-UNV	2"	14 W	1230 lm	91	2700, 3000, 3500, 4000, 5000 K	120 / 277 / 347V Triac, ELV, and 0-10V dimming
RGR2SQHP-CC-UNV	2"	14 W	1200 lm	91		
RGR4HP-CC-UNV	4"	20 W	1640 lm	92		
RGR4SQHP-CC-UNV	4"	20 W	1650 lm	92		

*ColorSelect+ is available for CDW models only. UNV models feature 5CCT (2700, 3000, 3500, 4000, 5000K)

*Energy Star certification applies to all models except RGR1-CDW

RGR1-CDWØ1-3/4" **RGR2-CDW**Ø2-3/4" **RGR2SQ-CDW**Ø2-3/4" **RGR4-CDW**Ø3-1/2" **RGR4SQ-CDW**Ø4-1/4" **RGR6-CDW**Ø6-3/8" **RGR6SQ-CDW**6" x 6" **RGR2HP-CC-UNV**Ø2-3/4" **RGR2SQHP-CC-UNV**Ø2-3/4" **RGR4HP-CC-UNV**Ø3-1/2" **RGR4SQHP-CC-UNV**Ø4-1/4" **Specifications**

Every fixture includes a junction box with integrated dimmable driver
 Universal voltage driver supports 120V, 277V, or 347V input with both TRIAC and 0-10V dimming
 Can be daisy chained (4" and 6" models only)
 Aluminum construction
 Switch-selectable CCT
 40° beam angle
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel (available for RGR4-CDW and RGR4SQ-CDW only)
- **WH** White

Accessories**REC-RFP-13**

Rough-in plate for RGR1

REC-RFP-2

Rough-in plate for RGR2, RGR2SQ, RGR2HP, RGR2SQHP

REC-RFP-35

Rough-in plate for RGR4, RGR4HP

REC-RFP-4, REC-RFPE4

Rough-in plate for RGR4SQ, RGR4SQHP

REC-RFP-6, REC-RFPE6

Rough-in plate for RGR6

REC-RFP-46SQ

Rough-in plate for RGR6SQ

RFP-UNI

Universal rough-in plate for RGR2, RGR2SQ, RGR2HP, RGR4SQ, RGR6, RGR6SQ

REC-CDW-EXT8FT, REC-CDW-EXT20FT

8 ft and 20 ft extension cables for CDW series

REC-CC-EXT8FT, REC-CC-EXT20FT

8 ft and 20 ft extension cables for UNV series

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.