

RGR

RGR4SQHP-CC-UNV

4" square high-powered regressed downlight

dals


PROJECT

DATE


TYPE

QTY

NOTES



LIGHT DISTRIBUTION



Distance from luminaire	FC at Nadir	Diameter
4'	280.2 fc	2'-5"
6'	124.5 fc	3'-7"
8'	70.1 fc	4'-9"
10'	44.8 fc	6'
12'	31.1 fc	7'-2"

*measured at 3000k

SPECS

Cut hole size (in)	4-1/4"
Watts (W)	20
Delivered lumens*	1650
Voltage (v)	120/277/347
FT rating	FT6
CRI	92
TM-30	Rf : 90 Rg : 100
Binning	3 SDCM
Beam angle (deg)	32
UGR	21
LED model	COB
Dimming	Triac / ELV / 0-10V
Color temperature	2700/3000/3500/4000/5000k

CONSTRUCTION

Lens material	Polycarbonate
Optic type	Optical lens

ELECTRICAL DETAILS

Location	Wet
Environment	Indoor/Outdoor
Operating temp. (° C)	-20 to 40
IP rating	IP65
Input voltage (V)	120-347
Input current (mA)	170 / 100 / 97
Output voltage (V)	33-37
Output current (mA)	450
Power factor (%)	97
Driver type	Constant current
THD	16.12
Lifetime @ L70	>50 000hrs

Finish type	Matte
Housing material	Aluminum

ORDERING GUIDE

RGR4SQHP-CC-UNV

-

Finish

WH - White



BK - Black



CERTIFICATIONS

ETL listed UL-1598 and CSA C22.2 No. 250.0

Title 24-JA8, Energy Star, IC rated, Air-tight ASTM E283-04

Compliant to FCC Title 47 Part 15; Class B

ICES-005 Issue 5



CANADA
80, Blvd. de la Seigneurie E.
Blainville, Quebec J7C 4N1

USA
4383, NW 124th Ave.,
Coral Springs, Florida 33065

1 877.430.1818
info@dals.com
dals.com

WHAT'S IN THE BOX

Recessed fixture

Junction box

3x push-in wire connectors

1/2" non-Metallic Connector

Instruction sheet

ACCESSORIES

REC-RFPE4

13" Rough-in template Ø4-1/4"

REC-RFP-4

26" Rough-in template Ø4-1/4"

RFP-UNI

Universal rough-in template

EXTENSIONS

REC-CDW-EXT8FT

96" extension cord for recessed fixtures

REC-CDW-EXT20FT

240" extension cord for recessed fixtures

WARRANTY

DALS offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DAL'S customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST**

BRAND	MODEL	DIMMER SPECS	DIMMING RANGE %		MAX LOAD (units)
			MIN	MAX	
Dals	SM-DIMSW Smart Dimmer*	Triac, 250W LED/CFL	7	100	12
Lutron	DVCL-153PR-WH-C*	Triac, 150 W Dimmable CFL/LED	4	100	7
Lutron	CTCL-153PDH-WH-C*	Triac, 150 W Dimmable CFL/LED	4	100	7
Lutron	STCL-153PH-WH-C*	Triac, 150 W Dimmable CFL/LED	11	100	7
Lutron	MACL-153MRHW-WHC*	Triac, 150 W Dimmable CFL/LED	0	100	7
Lutron	DVELV-300P-WH	ELV, 300W	11	100	14
Lutron	MA-PRO-WH*	ELV, 250W LED/CFL	2	100	12
Lutron	Caseta PD-6WCL-WH-R-C*	Triac, 300W Dimmable CFL/LED	4	100	7
Lutron	Caseta PD-5NE-WH-C*	ELV, LED—up to 250 W	8	100	12
Lutron	Caseta PD-10NXD-WH*	Triac, LED—up to 250 W	1	100	12
Leviton	DSM10-1LZ*	Triac, 450W Dimmable CFL/LED	5	100	21
Leviton	6674*	Triac, 150 W Dimmable CFL/LED	7	100	7
Leviton	PL06-10Z*	Triac, 150 W Dimmable CFL/LED	7	100	7
Leviton	DSL06-1LZ*	Triac, 300 W Dimmable CFL/LED	7	100	14
Legrand	ADTP703TUM4*	Triac,450W Dimmable CFL/LED	0	100	21
Control 4	C4-APD120-WH	ELV, 120W LED	2	100	6
Control 4	C4-FPD120-WH	Triac, 200W LED	2	100	9
TP-Link	HS220*	Triac, 150 W, Dimmable LED (MLV)	5	100	7
Lutron	DVSTV (0–10 V Controls)*	960W, 8A, 120–277 V	3	100	45
Leviton	IP710-DLZ(0–10 V Controls)	1200VA, 10A LED, 120-277V	2	100	56
Lutron	RMJS-8T-DV-B(0–10 V Controls)	960VA, 8A, 120-277V	1	100	45

*With low-end adjustment feature. **Some dimmers may produce minimal buzzing noise.



